

Hybrid DVR

8/16 CH Hybrid DVR

TD-2008TS-HL



TD-2116TS-HL



HD Output



DDNS



Network



PTZ



Audio



MIC



Mobile



CMS



USB



Mouse



E-mail

The series of product can connect analog and IP cameras simultaneously, which adopts the standard H.265 high profile compression format and the advanced SOC technique to ensure real time recording in each channel and realize outstanding robustness of the system. This series supports 8 / 16 CH video input, 1 / 1 CH audio input, simultaneous 8 / 16 CH playback.

The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.



en.tvt.net.cn

For more information, please visit our website

Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23rd Floor, Block B4, Building NO.9, Shenzhen Bay
Eco-Technology Park, Nanshan District, Shenzhen, Guangdong
Province, P.R.China

Tel: +86-755-36995888

Web site: <http://en.tvt.net.cn>

Fax: +86-755-33104777

E-mail: overseas@tvt.net.cn

SPECIFICATIONS


Model		TD-2008TS-HL	TD-2116TS-HL	
System	OS	Embedded Linux		
Video	Analog Video Input	BNC × 8	BNC × 16	
		BNC interface (1.0Vp-p; 75Ω)		
		TVI/AHD/CVI: 1080P/1080P Lite/720P/720P Lite/WD1		
	IP Video Input	2CH (up to 10CH)	2CH (up to 18CH)	
		Up to 5MP@25fps/4MP@30fps		
	Total Input	10CH	18CH	
	Output	HDMI × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 CVBS: No	HDMI × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 BNC × 1: CVBS(used as the main or spot output)	
Compression	H.264/H.265			
Audio	Input	RCA × 1		
	Output	RCA × 1 (linear, 600Ω)		
	Two-way audio	Take up channel one audio input		
	Compression	G.711(U/A)		
Record	Resolution	1080P Lite/720P/720P Lite/WD1		
	Frame Rate	Analog Channel: 1080P Lite/720P: 25fps (PAL)/30fps (NTSC) (only CH 1 supports) 1080P Lite/720P: 12fps (PAL)/15fps (NTSC) (other channels support) 720P Lite/WD1: 25fps(PAL) / 30fps(NTSC) IP Channel: 25fps(PAL) / 30fps (NTSC)		
	Bit Rate	32Kbps ~ 4Mbps		
Playback	Playback	8CH	16CH	
	Search	Time slice / time / event / tag search		
	Smart Search	Highlight colors to display the camera record in a certain period of time, different colors refer to different record events		
	Function	Play, pause, FF, FB, digital zoom, etc.		
Alarm	Mode	Manual, motion, exception, smart event		
	Input	No		
	Output	No		
Network	Interface	RJ 45 100Mbps × 1		
	Protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, HTTP, HTTPS, NTP, SMTP		
	Incoming Bandwidth	16Mbps (Max. 56Mbps)	16Mbps(Max. 80Mbps)	
	Outgoing Bandwidth	60Mbps	80Mbps	
MobileDevice	OS	iOS, Andriod		
Storage	HDD	SATA× 1, up to 6TB	SATA× 1, up to 8TB	
Backup	Local Backup	U disk, USB mobile HDD		
	Network Backup	Yes		
Port	RS 485	No		
	USB	USB 2.0 × 2		
	Remote Controller	No	Optional	
Others	Power Supply	DC12V / 1.5A	DC12V /2A	
	Consumption	≤ 5W (without HDD)	≤ 10W (without HDD)	
	Dimensions(mm)	255 × 222 × 42 (W × D × H)	255 × 234 × 42 (W × D × H)	
	Working Environment	-10~50°C, 10%~90% (humidity)		
	Certificate	CE, FCC		
Environment Protection	Comply with Directive EU RoHS, WEEE, REACH			

FEATURES


- 8 / 16 CH TVI / AHD/CVI 1080P/1080PLite/720P/720P Lite/WD1 video input
- 8 / 16 CH DVRs support 2 / 2 CH 5MP / 4MP / 3MP / 1080P / 960P / 720P IP video input by default
- 8 / 16 CH DVR default supports 8 / 16 CH analog input switched to IP input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- Multi-mode recording: manual / timer / motion / smart event
- Playback : 8 / 16 CH simultaneously playback
- Search: time slice, time, event, tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log review and device status review
- Support 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Android OS

DIMENSIONS

TD-2008TS-HL




TD-2116TS-HL



Rear Panel

TD-2008TS-HL



TD-2116TS-HL

