

C14

4MP Cube Wi-Fi Network Camera



- Max. resolution: 4MP (2560×1440)
- ICR auto switch, true day/night
- 0.3-10m IR night view distance
- 3D DNR, BLC, HLC, etc.
- Support dual streams
- Support 2.4G Wi-Fi
- Support mobile app for remote management and viewing of devices
- DC12V/PoE power supply
- Support P2P

Shenzhen TVT Digital Technology Co., LTD.

Address: 23rd Floor, Block B4, Building NO.9, Shenzhen Bay Eco-Technology Park, Nanshan District, Shenzhen, Guangdong Province, P.R. China

Tel: +86-755-36995888

Website: <http://en.tvt.net.cn>

Fax: +86-755-33104777

E-mail: overseas@tvt.net.cn

Specifications

| Model | C14 |
|----------------------------|--|
| Camera | |
| Image Sensor | 1/3" Progressive Scan CMOS |
| Image Size | 2560×1440 |
| Electronic Shutter | 1/3 s ~ 1/100000s |
| IRIS Type | Fixed IRIS |
| MIN. Illumination | Color: 0.0035lux@F1.2,AGC ON; B&W: 0 lux with IR |
| Lens | 2.1mm @F2.1; horizontal field of view: 137° |
| Lens Mount | M12 |
| WDR | 78dB |
| BLC | Yes |
| HLC | Yes |
| Defog | No |
| DNR | 2D/3D NR |
| Angle Adjustment | Pan: 0°~230°; Tilt: 0°~71°; Rotate: 0°~360° |
| Image | |
| Video Compression | Main stream: H.265+/ H.265/H.264+/H.264 Sub stream: H.265+/ H.265/H.264+/H.264/MJPEG |
| H.264 Compression Standard | Baseline Profile/Main Profile/High Profile |
| Bit rate Type | VBR/CBR |
| Bit Rate | 64Kbps ~ 6Mbps |
| Resolution | 4MP (2560×1440), 3MP (2304×1296), 1080P (1920×1080), 720P(1280×720), D1 |
| Main Stream | 60Hz:4MP/3MP/1080P/720P (1~30fps); 50Hz: 4MP/3MP/1080P/720P (1~25fps) |
| Sub Stream | 60Hz: 720P/D1/CIF (1~30ps); 50Hz: 720P/D1/CIF (1~25ps) |
| Image Setting | Saturation, hue, brightness, contrast, wide dynamic range, sharpness, NR, image flip, etc., adjustable through client or web browser |
| Audio Compression | G711A/U |
| Region of Interest | 8 regions of interest; each region can be configured separately |
| APP/Cloud | |
| WiFi Configuration | Configure Wi-Fi network by scanning the QR Code |
| Snapshot | Yes |
| Record | Yes |
| Two-way Audio | Yes |
| Listen | Yes |
| Storage | SD card storage |
| Playback | SD card storage |
| Sharing Device | Support sharing with friends |
| Interface | |
| Network Interface | 100M RJ45 |
| Audio | Built-in MIC×1, built-in speaker×1; echo cancellation supported |
| Alarm | 1CH alarm input; 1CH alarm output |
| Reset Button | Yes |
| PIR | Horizontal angle: 100°; Range: 5m |
| Storage | Built-in micro SD card slot, up to 128G |
| WiFi | 2.4G WiFi function, IEEE802.11b/g/n Up to 50m wireless range |
| Indicator | Yes |

| Function | |
|--------------------------|---|
| Remote Monitoring | IE client/mobile APP client |
| Online Connection | Support simultaneous monitoring for up to 3 users and multi-stream real time transmission |
| Network Protocol | UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, SNMP, FTP, 802.1x, UPnP, HTTPS, HTTP, HTTP POST, RTMP, QoS, P2P |
| Interface Protocol | ONVIF |
| Storage | Network remote storage |
| Smart Alarm | Motion detection, sensor alarm, PIR alarm, audio alarm, Person detection alarm, SD card full, SD card error, IP conflict, cable disconnection |
| Intelligent Analytics | Video exception (scene change, video blur and abnormal color detection) |
| General Function | Watermark, IP address filtering, video mask, illegal login lock |
| IR Light Distance | 0.3-10m |
| Water-proof Grade | No |
| PoE | Yes, IEEE802.3af |
| Others | |
| Power | DC12V/POE |
| Power Consumption | <5W |
| Environmental Protection | RoHS 2.0, REACH, WEEE, directive94/62/EC |
| Working Environment | -20°C~50°C, Humidity: less than 95% (non-condensing) |
| Dimensions(mm) | 130mm×71.7mm×71.7mm |
| Weight (net) | Approx.0.14KG |
| Installation | Wall mounting; Ceiling mounting; desktop mounting |

Available Model

| | | |
|-----------------|-----|-------------------------------|
| Available Model | C14 | 4MP Cube Wi-Fi Network Camera |
|-----------------|-----|-------------------------------|

Dimensions

